

-  ALL-IN-ONE
-  MOBILITY
-  MODULAR
-  PANELS PC
-  PRINTERS
-  DISPLAYS
-  ACCESSORIES

www.ares.com

# OCD 300/350

Customer Graphic Display Units



Compact, contemporary designed customer display units

The clean and compact contemporary design of the **OCD 300** (stand version) and of the **OCD 350** (pole version) customer display units is in perfect harmony with the spirit of AURES POS systems.

Fitting any sales counter, these peripherals can be tilted (0°- 90°), making them very adaptable and saving essential space.

Their multilingual high-quality graphic display (LED backlighting – two 20-character display lines) is an advantage.

They are equipped with a single, integrated USB cable for both power supply and data transmission.



# OCD 300/350



- Compact till point design
- 90° tilt angle
- High-quality, extremely bright, multilingual graphic display
- Single USB cable for data transmission and power supply
- ESC/POS compatible
- Serial port emulation



MODEL	OCD 300	OCD 350
Display mode		White LED backlighting FSTN negative transmissive LCD
Display colour		white /black
Number of characters		40 characters (2 lines x 20 characters)
Character matrix		12 x 32 points
Character size		6.33 mm x 16.93 mm
Character type		96 alphanumeric characters 28 international fonts
Brightness		700 cd/m2
Power supply		+5 V via USB plug
Electricity consumption		0.3 W
Reliability Centered Maintenance (RCM)		50,000 operating hours
Display panel dimensions		130.2 mm (width) x 37.6 mm (height)
Angles of view		30°- 60° (vertical) Minus 45°- 45° (horizontal)
Tilt angle		0°- 90°

ENVIRONNEMENT		
Operating temperature	5 °C- 45 °C	
Storage temperature	-10 °C - 55 °C	
Dimensions (L x H x D)	148 x 108 x 95 mm	148 x 258 x 95 mm
Weight	420 g	470 g

Specifications are subject to change without notice - © AURES 2016