



ALL-IN-ONE



MOBILITY



MODULAR



PANELS PC



PRINTERS



DISPLAYS



ACCESSORIES

www.ares.com

OLC 10.1

Additional promotional screen



Designed for POS digital signage applications

This secondary, adjustable **10.1-inch** non-touch screen has been developed for digital signage applications; it is the perfect equipment to entertain queuing customers, to build loyalty campaigns and to run ad' campaigns.

It is available in two versions - standalone (external) or integrated into the **Sango EPOS** system:

- the standalone version is an addition to any associated EPOS and can be positioned on the check-out counter.
- in its integrated version, the **OLC 10.1** is attached at the back of the **Sango** terminal's touch-screen, forming a complete dual-screen system (sango Evolution).

The **OLC 10.1** screen is adjustable, has LED backlighting, 1024 x 600 px fixed resolution, and 250 cd/m² brightness.



OLC 10.1



MODEL OLC 10.1

LCD Panel	10,1" - non touch
Brightness	250 cd/m ²
Resolution	1024 x 600 (fixed)
Viewing angle	(left, right, top, bottom) 70° / 70° / 50° / 70°

CONNECTIONS

1 USB cable (power and data) for the standalone version

ENVIRONNEMENT

EMC & Safety	CE, FCC Class A, LVD
Operating temperature	0 ~ 40°C
Storage temperature	-20 ~ 60°C
Humidity level (while operating)	20% to 80% RH - condensation-free
Humidity level (storage)	20% to 85% RH - condensation-free
Dimensions (H x W x D)	standalone version: 190 x 265 x 95mm (7.5" x 10.4" x 3.7") Sango-integrated version: 172 x 263 x 14 mm (6.8" x 10.3" x 0.5")
Weight	standalone version: approximately 1.06 kg (2.3lbs)
Fixings	for the standalone version only 75 x 75 VESA standard



Specifications are subject to change without notice - © AURES 2016