

















Omnidirectional Laser Scan Module

PS 75 is a laser scan module that delivers outstanding scanning performances in an easy-to-integrate unit, for any existing equipment – or kiosk, including point of sale or service applications. With its omnidirectional laser scan engine, **PS 75** performs 5 directions of scan field with a total 20 lines.

Along with 650nm visible laser diode and 20cm long-range scan field, it drives up to 1,400 scans per second; it is supplied with multiple interfaces - keyboard, RS-232C, USB and wand.

User-friendly, ergonomic design High performance Multiple interfaces





| MODEL | PS 75 |
|----------------------|---------------------------------|
| Light source | 650nm visible laser diode |
| Depth of Scan Field | 0-280mm@ UPC/EAN 100%, PCS 90% |
| Number of Scan Lines | 20 |
| Scan Pattern | 5 directions of scan field |
| Scan Speed | 1400 scan per second |
| Minimum Bar Width | 5mil @ PCS 90% |
| Print Contrast | 30% @ UPC/EAN100% |
| Indicators (LED) | two-color LED (red and green) |
| Beeper Operational | Programmable tone and beep time |
| System Interfaces | Keyboard, RS-232C, USB1.1, Wa |
| | |

| Input Voltage | 5VDC+10% |
|-------------------|--------------------------------------|
| Power | 1.0Watts |
| Operating Current | 200mA@ 5.0V |
| Laser Class | CDRH Class IIa, IEC 60825-1: Class 1 |
| EMC | CE&FCC DOC compliance |

| EIGVIKOIGIVIEIGI | | |
|-----------------------|--------------------------------|--|
| Operating Temperature | 0 à 40° C (32° F- 104° F) | |
| Storage Temperature | - 20° à 60° C (-4°F – 140°F) | |
| Humidity | 5%-95% RH (non-condensing) | |
| Light Level | max. 4500LUX (fluorescent) | |
| Shock | Designed to withstand 1m drops | |

| PHYSICAL | | |
|------------------------|----------------------|--|
| Dimensions (L x W x H) | 70 x 64 x 68mm | |
| Weight | 175g | |
| Cable | Standard 2m straight | |
| Colour | graphite black | |



POWER

ENVIRONMENT



