

- ALL-IN-ONE
- MOBILITY
- KIOSK
- PANELS PC
- PRINTERS
- DISPLAYS
- ACCESSORIES

YUNO KIOSK 22/27"

compact, multi application
integrated systems



All in one OEM & POS systems for wall mounted and kiosk applications

YUNO Kiosk is a robust and compact equipment, designed by AURES to suit the many applications of the OEM, Kiosk and POS vertical sectors.

This fanless high-performance hardware, fitted either with a Broadwell i5 5010U or a i3-5010U - or also a Quad-Core Bay Trail platform, is available in 2 wide (16/9) formats of 21.5" and 27,1". It is equipped with a shock- and scratch-proof, multi-touch, projected, capacitive screen (PCAP technology).

Very flexible, the YUNO Kiosk 22 & 27" range is offered with VESA fixings, for easy integration, wall mount and kiosk installations.

The products feature a 128 GB flash disk (2.5" SSD) and stand up to dirt in the toughest settings (*fat, crumbs, dust, splashes and leftovers...*).

They integrate energy efficient processors and a heat-dissipating aluminium structure, ensuring compliance with environmental standards (*low carbon footprint*).

The YUNO Kiosk 22 & 27" are accessible products, whose many features (technology, ergonomics, innovation and design) make them good value for money. They constitutes a sensible, cost-effective and long-term investment for your IT equipment.



YUNO KIOSK 22/27"



- Compact, heavy duty but stylish integrated systems
- Choice of 3 processors (energy efficient and low carbon footprint)
- 2.5" 128GB SSD (2 slots)
- Projected, capacitive, multi-touch screen (PCAP)
- 4 GB memory as standard (upgradable to 8 GB)
- Discreet yet easily accessible connectivity
- Mini DP output for 2nd screen (with i3 and i5 processors)
- Available with VESA bracket option(s), for wall or pole mounting installations



MODEL YUNO KIOSK 22/27"

Processor	Broadwell i5-5350U or i3-5010U - or BayTrail J1900 Quad Core (choice of 3 processors)
RAM	DDR3 SODIMM 4 GB as standard (up to 8 GB)
SSD	2.5" 128 GB (2 slots)
LCD	21,5" TFT or 27.1 TFT - 1920 x 1080
Touchscreen	Flat, zero bezel multi-touch screen – with projected, capacitive panel (PCAP)
Brightness	250 cd/m ² (22 ") and 270 cd/m ² (27")

INPUT-OUTPUT PORTS

Serial	4 serial ports (+ 5/12 V power supply for COM3 / COM4)
USB	5 USB 2.0 ports + 1 USB 3.0 port (for the J1900 version) 4 USB 2.0 + 2 USB 3.0 (for the i3 version)
LAN	10/100/1000Base-T
2 nd Screen	Port with support for HDMI, DVI and VGA (mini Display Port) on the i3 and i5 versions
Audio	Internal loudspeaker, headphones, micro jack plug
Power Supply	+ external 19 V DC
Mini-PCI Express	1 Mini PCI Express slot (WIFI)

MISCELLANEOUS

EMI	CE/FCC Class A
Safety	LVD, external adaptor UL c/us, CE, TUV, etc.
Operating Temperature	0 ~ 50°C
Front	Dust- and splash-proof IP 65
Colours	Black
Materials	Polycarbonate (cover) + aluminium (structure)
VESA	75 x 75
Dimensions (W x D x H)	517.44 x 313.31 x 54.08 mm (22") 644.60 x 385.03 x 64.10 mm (27")
Weight	5.5 kg (22 "), 8.04 kg (27")
Compatible OS	Windows 10 IoT Enterprise, Windows 8.1 Industry Pro, Windows 7 Pro, POSready 7, Linux

OPTIONAL EXTRAS

WIFI/Bluetooth	Combo WIFI 802.11 a/b/g/n + BT 4.0
----------------	------------------------------------



Specifications are subject to change without notice - © AURES 2020