

PRESS RELEASE

ODP 333 from AURES: Soon available in white

Lisses - Runcorn 11. December 2013. The new generation **ODP 333** receipt printer from the **AURES** Group has dressed itself up in white for the Christmas and New Year celebrations; the pure white lacquered surface, with mirrored reflections, enhances its contemporary look, in perfect harmony with the style of the latest generation of AURES EPOS terminals.

- The ODP 333 is very compact compared to traditional EPOS receipt printers. It features a cubic design with elegant black or white matt and gloss finish.
- It has a very ergonomic, splash-proof front receipt print-out, providing optimal protection against dust, crumbs and splashes in tough settings (kitchens, restaurants, cafés, baker's shops, etc.).
- The ODP 333's low energy consumption motherboard (*Energy Star certified*) switches it to standby mode as soon as it is no longer in use. This guarantees reduced electricity consumption *an average of 30% less* in line with new environmental standards for green technology.

The ODP 333 printer will be available in white from early 2014.

The ODP 333's plus points





- EPOS printer with contemporary cubic design (very ergonomic format)
- Low energy consumption motherboard (consumes less electricity)
- Triple interface: RS-232-C,, USB and Ethernet
- Front receipt print-out for a splash-proof, more watertight design, especially in tough café, hotel and restaurant settings.
- Print speed: 160 mm/sec
- Configuration utility
- All cables supplied
- Integrated buzzer
- Available in black or white

(See the full technical data sheet below)





About the AURES Group

Founded in 1989 and listed on Euronext since 1999, **AURES** manufactures electronic points of sale terminals and systems – together with related peripherals. This PC-based, open-system (*EPOS hardware*) is designed to provide management and till functions in specialist food and non-food stores, retail outlets, superstores or the catering and hospitality industry - and all other points of sale and service.

The **AURES Group** - which includes **AURES Technologies** and **J2 Retail Systems** - has global presence, with its head office in France, subsidiaries in Great Britain, Germany, Australia and the USA - and a network of distributors and resellers located in more than 50 other countries.

In 2013, the **AURES** Group represents over 50,000 deployed systems and sales in excess of €50 million.

For additional information, please contact:

Yannick-Florence WAELLY

+33(0)1 69 11 16 65 (LD)

yannick.waelly@aures.com

www.aures.com



The Sango Pack with white ODP 333 receipt printer

(Photos AURES 2013)



ODP 333 - Technical features

iffective Print Width Characters per line Font A: 42 columns, 180dpi Font B: 156 columns, 180dpi Font B: 156 columns, 180dpi / 64 columns, 203dpi Internal memory Forther Side Columns, 180dpi / 64 columns, 203dpi Internal memory Forther Side Columns, 180dpi / 64 columns, 203dpi Internal memory Forther Side Columns, 180dpi / 64 columns, 203dpi Internal pager Width Forther Side Columns F	Print method	direct, thermal
theracters per line Font A: 42 columns, 180dpi / 64 columns, 203dpi font B: 56 columns, 180dpi / 64 columns, 203dpi nternal memory Motherboard low power consumption — automatic standby mode enables 30% less power use on average automatic finermal paper Width 79.5mm +/- 0.5mm Mickness 0.065 = 0.1mm Max. roll diameter Sharacters Wighan uneric 95 textended graphic 128 x 18 pages International characters 14 Barcode UPC - A. UPC - E. FAN - 8. Code 39. Code 128. ITE Codabar . 20 PDF417. OR Code imulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) / OPOS / Linux / Java POS ensor end-of-roll, near end-of-roll, cover open fill output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Interfaces Triple interface R5232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Integrated buzzer Paper cutter Auto cutter guillotine type Max. 30 cuts/minute total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 150km Paper cutter lifespan: 15	Print speed	160mm/sec
Font B: 56 columns, 180dpi / 64 columns, 203dpi Adotherboard low power consumption – automatic standby mode enables 30% less power use on average automatic Adotherboard automatic Adotherboard enables 30% less power use on average automatic Adotherboard automatic Ad	Effective Print Width	72mm / 512 dots/line
Internal memory 64MB Motherboard low power consumption – automatic standby mode enables 30% less power use on average automatic Paper loading automatic Thermal paper Width 79.5mm +/- 0.5mm Max. roll diameter 83mm Alphanumeric 95 Alphanumeric 95 Alphanumeric 128 x 18 pages International characters 14 International characters 14 International characters 14 International characters 15 International characters 16 International characters 17 International characters 17 International characters 18 International characters 19 International characters	Characters per line	Font A: 42 columns, 180dpi
low power consumption – automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on average automatic standby mode enables 30% less power use on 30% less power supply automatic standby mode enables 30% less power use on 30% less power use and paper thickness power use and lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 160km Paper utter lifespan: 160km Pap		Font B: 56 columns, 180dpi / 64 columns, 203dpi
enables 30% less power use on average automatic Thermal paper Width 79.5mm +/- 0.5mm Chickness 0.065 – 0.1mm Bamm Characters Wighanumeric 95 Extended graphic 128 x 18 pages International characters 14 Barcode UPC - A, UPC-E, EAN-B, Code 39, Code 128, ITF, Codabar, ZD PDF417, DR Code ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS ensor end-of-roll, near end-of-roll, cover open Illi output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interfaces Printer face RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter guillotine type Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Oberating temperature - 20 to +60°C Operating temperature - 20 to +60°C Operating humidity 10% to 90% (without condensation) Dirensions (depth x width x height) 16 x x 135 x 105.02mm Weight 1 kg approximately	Internal memory	64MB
Ager loading automatic Thermal paper Width 79.5mm +/- 0.5mm Dickness 0.065 - 0.1mm Max. roll diameter 83mm Characters Alphanumeric 95 Extended graphic 128 x 18 pages International characters 14 Barcode UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codebar, ZD PDF417, OR Code Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) / OPOS / Linux / Java POS Bensor end-of-roll, near end-of-roll, cover open fill output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interfaces Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) Power supply External 24V - 1,75A Integrated buzzer Paper cutter Auto cutter guillotine type Max. 30 cuts/minute Cut type 1 day 35-50 million lines depending on type of use and paper thickness Printer features MCBF 35-50 million lines depending on type of use and paper thickness Printer features MCBF 35-50 million lines depending on type of use and paper thickness Printer features per cutter (Ifespan: Approx. 1.5 million cuts) Deperating temperature -20 to +60°C Deperating humidity 10% to 90% (without condensation) Differsions (depth x width x height) 165 x 135 x 105.02mm Weight 18g approximately	Motherboard	low power consumption – automatic standby mode
Thermal paper Width 79.5mm +/- 0.5mm Thickness 0.065 – 0.1mm Max. roll diameter 83mm Characters What will diameter 95 Statended graphic 128 x 18 pages International characters 14 Barcode UPC - A. UPC-E, FAN-8, Code 39, Code 128, ITF, Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Sensor end-of-roll, near end-of-roll, cover open Itili output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interfaces RS232 Serial - USB & Ethernet dual (non-modifiable) Power supply External 24V - 1,75A Therefaces under a guillotine type Max. 30 cuts/minute Lut type total or partial Charter features WICBF 35-50 million lines depending on type of use and paper thickness Printer head ilfespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 160km Paper cutter lifespan: 150km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Weight 1kg approximately		enables 30% less power use on average
Avide the Avide to	Paper loading	automatic
Thickness 0.065 – 0.1mm Max. roll diameter 83mm Characters Mphanumeric 95 Extended graphic 128 x 18 pages International characters 14 Iarcode UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS /	Thermal paper	
Abaracters Alphanumeric 95 Extended graphic 128 x 18 pages International characters 14 Barcode UPC - A, UPC-E, EAN-8, Code 39, Code 128, ITF, Codabar, 2D PDF417, QR Code ESC/POS compatible Drivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emulation ESC/POS compatible Drivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Emsor end-of-roll, near end-of-roll, cover open Till output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface R5232 Serial - USB & Ethernet dual (non-modifiable) Power supply External 24V - 1,75A The page cutter Abar 30 cuts/minute Cut type Max. 30 cuts/minute Total or partial Defer features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Meight 1kg approximately	Width	79.5mm +/- 0.5mm
Characters Alphanumeric Extended graphic I28 x 18 pages International characters 14 Jarcode UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF. Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Orivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Gensor end-of-roll, near end-of-roll, cover open fill output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Integrated buzzer Paper cutter Auto cutter guillotine type Max. 30 cuts/minute Cut type Total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 18g approximately	Thickness	0.065 – 0.1mm
Alphanumeric 95 Extended graphic 128 x 18 pages International characters 14 UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Sensor end-of-roll, near end-of-roll, cover open Itill output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Interfaces Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter guillotine type Max. 30 cuts/minute Cut type total or partial Other features WCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Itis approximately Itis approximately Neight 18g approximately	Max. roll diameter	<u>83mm</u>
I 128 x 18 pages International characters I 14 Iarcode IPC - A, UPC-E, EAN-B, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Sensor end-of-roll, near end-of-roll, cover open If lid output port(s) I dual port (for 2 drawers) - RJ11 6-pin connector Irriple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter guillotine type Max. 30 cuts/minute total or partial Deter features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 1 kg approximately	Characters	
I 128 x 18 pages International characters I 14 Iarcode IPC - A, UPC-E, EAN-B, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Sensor end-of-roll, near end-of-roll, cover open If lid output port(s) I dual port (for 2 drawers) - RJ11 6-pin connector Irriple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter guillotine type Max. 30 cuts/minute total or partial Deter features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 1 kg approximately	Alphanumeric	95
nternational characters 3arcode UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 20 PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) / OPOS / Linux / Java POS Gensor end-of-roll, near end-of-roll, cover open Itili output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Decrating temperature -20 to +60°C Decrating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 1 kg approximately	Extended graphic	 128 x 18 pages
Codabar, 2D PDF417, QR Code Emulation ESC/POS compatible Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Gensor end-of-roll, near end-of-roll, cover open Itil output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) Power supply External 24V - 1,75A Paper cutter Auto cutter guillotine type Max. 30 cuts/minute Cut type total or partial Diher features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight	International characters	14
Exc/POS compatible Drivers Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS Bensor end-of-roll, near end-of-roll, cover open Till output port(s) 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute Cut type Diher features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) Reight 1kg approximately	Barcode	UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF,
Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS sensor end-of-roll, near end-of-roll, cover open 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface R5232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter guillotine type Max. 30 cuts/minute Cut type total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight		Codabar, 2D PDF417, QR Code
Sensor end-of-roll, near end-of-roll, cover open 1 dual port (for 2 drawers) - RJ11 6-pin connector Interfaces Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute Cut type Max. 30 cuts/minute Total or partial Define features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature Deparating temperature Deparating humidity Definensions (depth x width x height) Deparating temperature Deparating temperature Deparating humidity Definensions (depth x width x height) Definensions (depth x width x height) Reight	Emulation	ESC/POS compatible
Triple interface Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity Dimensions (depth x width x height) Neight 1 dual port (for 2 drawers) - RJ11 6-pin connector Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Suillotine type Max. 30 cuts/minute total or partial	Drivers	Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS
Triple interface RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute total or partial Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating temperature Deparating temperature 10% to 90% (without condensation) Dimensions (depth x width x height) Reight 1kg approximately	Sensor	end-of-roll, near end-of-roll, cover open
RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deperating temperature -20 to +60°C Deperating humidity Dimensions (depth x width x height) Meight RS232 Serial - USB & Ethernet dual (non-modifiable) External 24V - 1,75A Suillion type Max. 30 cuts/minute total or partial	Till output port(s)	1 dual port (for 2 drawers) - RJ11 6-pin connector
Power supply External 24V - 1,75A Paper cutter Auto cutter Max. 30 cuts/minute Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity Dimensions (depth x width x height) Meight External 24V - 1,75A Suillotine type Max. 30 cuts/minute total or partial	Interfaces	Triple interface
Paper cutter Auto cutter Max. 30 cuts/minute Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature Deparating humidity Dimensions (depth x width x height) Meight Paper cutter lifes x 135 x 105.02mm Meight Auto cutter guillotine type Max. 30 cuts/minute total or partial		RS232 Serial - USB & Ethernet dual (non-modifiable)
Paper cutter Auto cutter Max. 30 cuts/minute Cut type Dither features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) Meight 1kg approximately	Power supply	External 24V - 1,75A
Auto cutter Max. 30 cuts/minute	Integrated buzzer	
Auto cutter Max. 30 cuts/minute		
Max. 30 cuts/minute total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Oimensions (depth x width x height) 165 x 135 x 105.02mm Neight Neight	Paper cutter	and the state of the state of
Cut type total or partial Other features MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Oimensions (depth x width x height) 165 x 135 x 105.02mm Neight Neight	Auto cutter	
MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately	Cut type	
MCBF 35-50 million lines depending on type of use and paper thickness Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Deparating temperature -20 to +60°C Deparating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately		
Printer head lifespan: 160km Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Oimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately	Other features	
Paper cutter lifespan: Approx. 1.5 million cuts Operating temperature -20 to +60°C Operating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately	MCBF	35-50 million lines depending on type of use and paper thickness
Departing temperature -20 to +60°C Departing humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately		
Diperating humidity 10% to 90% (without condensation) Dimensions (depth x width x height) 165 x 135 x 105.02mm Neight 1kg approximately		Paper cutter lifespan: Approx. 1.5 million cuts
Dimensions (depth x width x height) Neight 10% to 90% (without condensation) 165 x 135 x 105.02mm 1kg approximately	Operating temperature	-20 to +60°C
Neight 1kg approximately	Operating humidity	10% to 90% (without condensation)
	Dimensions (depth x width x height)	165 x 135 x 105.02mm
Colours Black or White	Weight	1kg approximately
	Colours	Black or White