

PRESS INFORMATION

AURES introduces **Yuno** VESA

This robust EPOS system - yet the most stylish hardware in its category - is now presented in its VESA version, for dedicated wall or pole-mounted applications.

Lisses, Runcorn - April 2015; the VESA version of AURES' Yuno terminal is announced: flexible, adaptable and multi-application, the latest EPOS in AURES point of sale systems' range is now available in 2 new configurations:

- supplied without its traditional base (stand), the point-of-sale system can be wall-mounted, ideal for retail applications where space is tight and where operators stand most of the time at point of purchase.
- The VESA option also enables the terminal to be located on a pole either articulated or not and thus positioned at the optimum eye level, for improved ergonomics and greater comfort of both users and customers.

Just like the standard model, the **Yuno VESA** option stands up to dirt in the toughest settings (fanless sytem with PCAP multitouch panel resisting fat, crumbs, dust, splashes, and leftovers in kitchens, restaurants and bakeries). The energy efficient Bay Trail J1900 processor (consuming just 10 W), together with the heat-dispersing aluminium structure, prevents overheating and ensures compliance with current environmental norms.

Robust, reliable and accessible, **Yuno VESA** offers many advantages (technology, ergonomics, innovation and design) which make it good value for money. It is a sensible, cost-effective and long-term investment for any EPOS IT equipment.

- Compact, heavy duty but stylish EPOS
- VESA bracket option(s), for wall or pole mounting installations
- Quad-core Bay Trail J1900 processor
- 2.5" 64 GB SSD (2 slots)
- Projected, capacitive, multi-touch screen (PCAP)
- 4 GB memory as standard (upgradable to 8 GB)
- Discreet yet easily accessible connectivity
- Energy efficient processor (10W) and low carbon footprint



About AURES Technologies - www.aures.com

Founded in 1989 and listed on Euronext since 1999, the AURES Group manufactures EPOS systems and related peripherals. Its PC-based hardware and open-system equipment provides management and till functions to all points-of-sale and points-of-service, including specialist food and non-food stores, retail outlets, superstores, restaurants and all catering & hospitality businesses.

With corporate sales over €64 million for 2014, the AURES Group has global presence, with its head office in France, subsidiaries in the UK, Germany, Australia and the USA - and a network of distributors and resellers in 50+ countries.

For any additional information, please contact:

Yannick-Florence WAELLY Communications & PR Manager 01 69 11 16 65 (LD)

yannick.waelly@aures.com



Yuno Vesa (wall mounted option)



Yuno Vesa (pole mounted option)



Data Sheet

Model	YUNO
Processor	BayTrail J1900 Quad-Core
RAM	DDR3 SODIMM 4 GB as standard (up to 8 GB)
SSD	2.5" 64 GB (2 slots)
LCD	15" TFT (1024 x 768)
LOD	or 15.6" (1366 x 768) (Yuno wide]
	LED back-lighting
Touchscreen	Flat, zero bezel-multi-touch screen – with projected, capacitive panel (PCAP)
Brightness	250 cd/m2
Input-Output Ports	
Serial	4 serial ports (+ optional 5/12 V power supply for COM3 / COM4)
USB	5 USB 2.0 ports + 1 USB 3.0 port
LAN	10/100/1000Base-T
2 nd Screen	Port with support for HDMI, DVI and VGA (mini Display Port) (optional)
Cash Drawer	24/12 V DC
Audio	Internal loudspeaker, headphones, micro jack plug
Power Supply	+ external 19 V D
Mini-PCI Express	1 Mini PCI Express slot (WIFI)
Miscellaneous	
EMI	CE/FCC Class A
Security	LVD, external adaptor UL c/us, CE, TUV, etc.
Operating Temperature	<u>0-40 °C</u>
Front	Dust- and splash-proof
Colours	Black or White
Materials	Polycarbonate (cover) + aluminium (structure)
Dimensions (W x D x H)	360.1 x 171.5 x 316.1 mm (15.1" format) 402.2 x 171.5 x 295.3 mm (15.6" Wide format)
Weight	10 - 11 kg depending on the option (15.1" format) 11 - 12 kg (15.6" Wide format)
Compatible OS	Windows 8 Industry, Windows 7 Pro, POS Ready 7, Linux, Androïd
Optional Extras	
MSR	3 ISO tracks, OPOS support
RFID / Addimat and/or Dalla	s readers 1 slot, at right of EPOS terminal
Bare-code scanners	1D & 2D
Fingerprint reader	Yes
Customer display	20 characters x 2 lines (VFD)
2 nd screen	10.1" - 16:9 1024 x 600 <u>Flat LED screen</u> (EPOS digital signage)
WIFI	Internal, 802.11 b/g/n
VESA fixings option(s)	For wall or pole-mounted applications (no base nor stand).

YUNO is compatible with many peripherals and all integrated sango EPOS terminal accessories.