



ALL-IN-ONE

www.ares.com



MOBILITY



KIOSK



PANELS PC



PRINTERS



DISPLAYS



ACCESSORIES

# KOSMOS

Self-Service Kiosk

## Compact self-supporting design



Ultra-stable thanks to its specific compact and self-supporting design, the **KOSMOS** kiosk fits on the floor without any fixings thanks to an adapted stand.

Its design reveals a controlled integration of high quality and high-performance sub-systems, the YUNO 15", 21.5" or 27" touch systems. Also receipt printing system with presenter/retract function and payment terminals.

KOSMOS is suitable for many retail businesses offering a range of takeaway sales, thanks to its multiple management application options: booking and order taking, click and collect, purchase and sales assistance, queue busting, subscription and customer loyalty card management and other promotional operations.



# KOSMOS



- 15", 21.5" or 27"
- 3 processors to choose from, J1900, i3 or i5
- 128 GB 2.5" SSD
- PCAP multi-touch panel
- Autonomous or centralized payment terminal (EFT)
- 80 mm thermal receipt printer with presenter and retract function
- 2D barcode reader



## MODEL YUNO KIOSK 15" - 21,5" - 27"

|             |   |
|-------------|---|
| Processor   | i5-5350U or i3-5010U Broadwell or Intel Bay trail J1900 |
| RAM         | DDR3 SODIMM 4 GB in standard – up to 8 GB               |
| SSD         | 2.5" 128 GB (2 slots)                                   |
| LCD         | 15" TFT (1024 x 768) or 21,5" or 27" TFT (1920 x 1080)  |
| Touchscreen | Flat & Edgeless PCAP Panel                              |

## OTHER SYSTEMS

|            |   |
|------------|---|
| Printer    | 80 mm thermal receipt printer with presenter and retract function |
| 2D scanner | Honeywell CF3680  |

## INPUTS-OUTPUTS

|                  |   |
|------------------|---|
| Serial ports     | 4 ports (+ 5/12V power supply for COM3/COM4)  |
| USB              | 5 x USB 2.0 + 1 USB 3.0 (J1900 model)<br>4 x USB 2.0 + 2 USB 3.0 (i5 and i3 models) |
| LAN              | 10/100/1000 Base-T  |
| Mini-PCI Express | 1 slot  |

## EFT

|           |                            |
|-----------|----------------------------|
| Worldline | Valina                     |
| Ingenico  | iSelf / LAN 5000 / IPP 350 |
| Verifone  | UX / P 400                 |
| PAX       | S 300                      |

## MISCELLANEOUS

|                           |  |                      |                    |
|---------------------------|--|----------------------|--------------------|
| CEM                       | CE Directive CEM 2014/30/EU (Class B)                              |                      |                    |
| Safety                    | CE Directive BT 2014/35/EU   |                      |                    |
| Operating Temperature     | 5 - 35° C  |                      |                    |
| Front Panel               | Splashproof & Dust Resistant (IP55)                                |                      |                    |
| Colours                   | black (other colour options with orders > 100 pieces)              |                      |                    |
| Dimensions (W x P x H cm) | 15': 43 x 49 x 132   | 21,5': 53 x 49 x 140 | 27': 63 x 49 x 142 |
| Weight                    | 15': 59 kg   | 21,5': 64 kg         | 27': 66 kg         |
| Compatible OS             | Windows 10 IoT Enterprise / Linux / Android (with J1900 processor) |                      |                    |

Specifications are subject to change without notice - © AURES - 2021